









MS 500 BENCH SAWS





FEATURES & BENEFITS

- Straight and accurate cutting is achieved through the use of a sliding table fitted with seize free rollers.
- Dust free operation from a highly reliable submersible pump.
- Fitted with wheels for ease of transportation.
- Cutting head can be raised or lowered by hand or foot.
- Extra large blade guard to take larger blades
- Machine splits in two for ease of transportation and storage.
- Easy to reach controls for added safety.
- Petrol or Electric options available.



FORKLIFT POINTS FOR SAFE ON-SITE TRANSPORTATION



EASY TO ACCESS CONTROLS FOR ADDED SAFETY

TECHNICAL SPECIFICATIONS

Model Part No.	MS500 Honda MS501		Model Part No. (110v)	MS 500 Electric MS507	
Engine Power	(Hp/kW)	5.5/4.1	Part No. (230v)	MS513	
Blade Size	(mm)	500	Motor Power	(Hp/kW)	3.5/2.5
Blade Speed	(rpm)	2256	Minimim Transformer	(kVA)	10
Max. Cut Length	(mm)	630	Blade Size	(mm)	500
Max. Cut Depth	(mm)	195	Blade Speed	(rpm)	2256
Water Tank Capacity	(Ltr)	57	Max. Cut Length	(mm)	630
Noise Level . ,	(dB(A))	104	Max. Cut Depth	(mm)	195
Width	(mm)	715	Water Tank Capacity	(Ltr)	57
Height	(mm)	1590	Noise Level	(dB(A))	107
Length	(mm)	1410	Width	(mm)	715
Weight	(kg)	202.5	Height	(mm)	1590
<u> </u>	. 3.		Length	(mm)	1410
			Weight	(kg)	202.5



