## Useful Reference Points • www.hae.org.uk/businessguard

Betore Starting Work.

## **TSARRA JJA** SELECTION OF EQUIPMENT -

1. It is recommended that a Full Body appropriate anchorage point. of a shock-absorbing lanyard connected to an

Purpose - To arrest any potential fall by means

- Arrest applications. points at rear or chest is used for hall Harness with appropriate connection
- fully closed and locked before use. connection. Check to ensure they are may have twist lock or screw type secured. Types, such as karabiners, 2. Ensure the lanyard connections are
- emergency occur. the removal this equipment should an the harness user, should be tamiliar with As a precaution, persons working near to 31

## TNIAATS3A JJA3 SELECTION OF EQUIPMENT -

the point of connection - normally by means potential of a fall by limiting the distance from Purpose – To restrain the user from the

ot a tixed lanyard.

FTH HIRE GROUP

v:042017

- connection points may be used for Fall Harness with appropriate side 1. It is recommended that a Full Body
- Restraint applications.

- The Crescent Birmingham Business Park nuou sinegen uce Association Europe

**3YT TEB Iludilos** 



effort has been made by HAE/EHA to ensure that the information given in this docun



1215 Safety Guidance

Full Body Harness, Rescue Harness

Fall Protection Equipment

Please note: Training is available from approved providers and is recommended for all users of Fall Protection Equipment.

It is important to read this entire leaflet BEFORE using **Fall Protection Equipment** 

Plan your work and think ahead to make sure you will always be working safely.

It is the responsibility of the user to inspect the Fall Protection Equipment fully before

Fall protection Equipment is comprehensively inspected at three monthly intervals by

a competent person. Evidence of this inspection should have been issued with the

The action and use of Fall Protection Equipment can cause injury or damage if the

If issued to arrest a fall, this Fall Protection Equipment must not be used again. Return

Only components supplied by the hire company must be used with this Fall Protection

Beams, joists and other projections within the vicinity of the user may impede the safe

Fall Protection Equipment must not be used by minors, or by anyone under the

This equipment is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.

11. Ensure that the Fall Protection Equipment is kept in a suitable container. Avoid heat and direct sunlight. If the equipment becomes wet, allow it to dry naturally before

12. Training is available and recommended from approved providers for all users of Fall

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments

have the force of law and only the courts can authoritatively interpret the law.

Lanyards for Fall Arrest purposes, Lanyards for Fall Restraint purposes

units (with winches).

suonsonge.

**RESCUE HARNESS** 

.s





































possible, dedicated retractable fall arrest

with suitable rescue lines and, where

connection points be used for Rescue

Harness with appropriate dedicated top

J. It is recommended that a Full Body

A namess specifically designed for arrest or

10 degrees from a vertical position (uprigni).

designed to ensure the user is no more than

positioning of the connection point is

ancu as ducts, tanks and silo's etc. the

Purpose - To be used in confined spaces,

Check to ensure they are fully closed

have twist lock or screw type connection.

secured. Types, such as karabiners may

Ensure the lanyard connections are

SELECTION OF EQUIPMENT -

and locked before use.

restraint applications MUST NOT BE USED.

5. Rescue harnesses should only be used



Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

©Copyright Hire Association Europe April 2011



be required for further information

Please store this leaflet safely. It may

immediately and contact the hire

ARE CONCERNED ABOUT USING IT

POINTS ARE IDENTIFIED OR IF YOU

EQUIPMENT IF ANY OF THE ABOVE

I hese units have visual indicators when

system has no evidence of damage.

ensure that any 'shock absorbing'

close secritely and they do not require

corrosion. Ensure that connections

evidence of distortion, cracks or

must be fully functional. Check fully for must be inspected and moving parts

7. Karabiners, connectors and buckles

8. Inspect the Fall Arrest lanyard unit to

**3HT 3SU TON OG - TNATROAMI .6** 

used in an 'Arrest' situation.

excessive force to operate.

ednibueur Itou

əsn

company.

эvотэЯ .01

X144AS

1.

2.

3.

4.

5.

6.

7

8.

9.

situation.

each and every use.

chemical contamination.

Hiro Association Euro 2450 Regents Court The Cr Birmingham Busi Solihull B37 7YE



For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

Before and after use...

It is the responsibility of the user to inspect the Fall Protection Equipment fully before

The hire company will have provided a current certificate or other proof of inspection

The length of lanyard for both Fall Arrest and Fall Restraint must not be extended

The webbing must be inspected fully - for evidence of fraying, cuts, discoloration, or

The webbing must be inspected fully - for evidence of wear, such as fraying or loose

Karabiners, connectors and bucklers must be inspected and moving parts must be

fully functional. Check fully for evidence of distortion, cracks or corrosion. Ensure that

Inspect the Fall Arrest lanyard unit to ensure that any 'shock absorbing' system has

no evidence of damage. These units have visual indicators when used in an 'arrest'

IMPORTANT - DO NOT USE THE EQUIPMENT IF ANY OF THE ABOVE POINTS ARE

Please keep this leaflet safely as it may be required for future reference

connections close securely and they do not require excessive force to operate.

IDENTIFIED OR IF YOU ARE CONCERNED ABOUT USING IT SAFELY.

Remove equipment from use immediately and contact the hire company.

that the equipment is safe for use. If not, check with the hire company.

beyond that of the original supplier's specification.

movement. All stitch patterns must be fully inspected.

e.org.uk www.hae.org.uk

All stitch patterns must be fully

damage or evidence of wear, such as

evidence of fraying, cuts discoloration, or

beyond that of the original supplier's

and Fall Restraint must not be extended

use. It not, check with the nire company.

inspection that the equipment is safe for

current certificate or other proof of

inspect the Fall Protection Equipment

3. The length of lanyard for both Fall Arrest

2. The hire company will have provided a

1. It is the responsibility of the user to

tully before each and every use.

**32U RATAA GNA AROABA** 

5. The webbing stitching must be free from

The webbing must be inspected fully – for

Itaying or loose movement.

chemical contamination.

specification.



121 380 4600 44 (0) 121 333 4109



































































inspected.

Includes:

1.

2.

3.

4.

5

6

7.

8.

9.

storage.

Protection Equipment.

hire

each and every use.

equipment is not used or worn correctly.

operation of the Fall Protection Equipment.

10. Do not leave the equipment unattended at any time.

Equipment to ensure compatibility.

influence of drugs or alcohol.

it to the hire company stating the nature of the incident.



















