



BLOCKAGES

- Take care to prevent blockages by appointing one or more responsible persons to monitor the use of the chute.
- Make sure the bottom section of the chute is a short distance above the maximum load level in the skip.
- Any item that has a larger dimension than the diameter of the chute must not be passed down the chute.
- Change to an empty skip before the one in use becomes overfull.
- Further use of the chute must be stopped once a blockage has occurred until it has been cleared.
- Blockages most frequently occur at the bottom section of the chute, because the skip is too full.
- Blockages must be cleared only under the direct supervision of a competent person, who should make proper arrangements to:
 - support the chute safely;
 - prevent injury from falling material;
 - ensure that all waste material is collected in the skips;
 - provide a safe working platform if needed for clearing blockages partway down the chute;
 - obtain whatever extra equipment is needed to clear the blockage safely.

WARNING !

Never use a blocked rubbish chute. Continuous use when blocked will result in a build up of material increasing the weight of the assembly and applying additional forces to the scaffolding, structure or fixing point/bracket.



Hire Association Europe
2450 Regents Court
The Crescent
Birmingham Business Park
Solihull B37 7YE

Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
website: www.hae.org.uk

©Copyright Hire Association Europe April 2011
Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

- ## WARNING !
- The chute should be dismantled by reversing the erection procedure.
 - Two from the bottom and the chute sections should be removed one by one from the bottom up according to the erection procedure.
 - Do not attempt to lower the chute until all blockages are cleared, all tie-in points are free and the skip is removed.
 - Do not attempt to lower the chute until all the top or a complete assembly can be undismantled resulting in personal injury/fall from height.

DISMANTLING THE RUBBISH CHUTE

- A suitable manual of power tools should be used to dismantle the chute.
- The chute sections should be arranged vertically in the skip frame system, supplied with the chute frame assembly.
- A scaffold frame assembly, supplied with the chute, connects to the scaffold and supports vertically.
- The chute sections should be reassembled as near vertical as possible.
- The chute frame assembly should be used to attach the chute frame to the horizontal position.
- Do not attempt to raise a fully assembled chute from the scaffold if possible.
- The chute sections should not be allowed to rest on the scaffold if possible.
- Chains, ropes, and metal fittings and clips that are of suitable strength must be used to attach the chute.

- The safe working load (SWL) of the which must be sufficient to lift the required number of chute sections.
- The safe working load (SWL) of the which must be sufficient to lift the required number of chute sections that can be connected together.
- If a long chute is planned to be erected, contact the hire company regarding the maximum number of sections that can be connected at a time.
- The chute which must only be used for lifting and lowering the which must be used to support the which is in use.
- If the chute is assessed by adding sections to the bottom, the which is then used to lift the next section used to lift the which is then used to lift the next section can be attached at the bottom.
- The chute must be secured to the which is in use.
- The which must be secured to the which is in use.
- The which must be secured to the which is in use.
- The which must be secured to the which is in use.
- The which must be secured to the which is in use.
- The which must be secured to the which is in use.

- The safe working load (SWL) of the which must be sufficient to lift the required number of chute sections.
- A scaffold frame assembly, supplied with the chute, connects to the scaffold and supports vertically.
- The chute sections should be arranged vertically in the skip frame assembly.
- The chute frame assembly should be used to attach the chute frame to the horizontal position.
- Do not attempt to raise a fully assembled chute from the scaffold if possible.
- The chute sections should not be allowed to rest on the scaffold if possible.
- Chains, ropes, and metal fittings and clips that are of suitable strength must be used to attach the chute.

USING THE RUBBISH CHUTE

- Keep a close check on the rubbish chute and all equipment at all times. If any item appears to be damaged, stop using the rubbish chute before inspecting it closely.
- Do not improvise any replacement for worn or damaged fittings. Only use replacements supplied by the hire company.
- Make sure that nobody interferes with the rubbish chute, or does anything that is likely to damage it.
- Do not use the chute to pass down anything that is flammable, or any materials that are hot and may set fire to or damage the chute.
- A competent person must check any scaffolding once a week. An inspection of the rubbish chute assembly should also be carried out.
- If the rubbish chute does not work properly, do not try to repair it. Contact the hire company.
- You may want to read this leaflet again. Please keep it until you have finished work.

Rubbish Chute

READ ENTIRE LEAFLET BEFORE USING RUBBISH CHUTE

There are rules and procedures in force that may require the person responsible for this equipment to carry out a specific risk assessment.
This leaflet is not a substitute for a properly executed risk assessment.

- This leaflet is intended for guidance on the safe setting up and operation of a rubbish chute.
- A competent person must take responsibility for the safe use of the rubbish chute.
- This rubbish chute is designed to provide a quick, safe method of transferring rubbish from a roof or similar high place to a rubbish skip at ground level.
- Plan ahead to ensure a safe operation.
- The following items of personal protective equipment must be worn as a minimum - goggles, dust mask - a minimum of EN149 FFP3(s) protection, safety boots and gloves.
- This rubbish chute must not be used by minors, or by anyone under the influence of drugs or alcohol.
- This rubbish chute is designed for erection and use by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.



Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting material is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments have the force of law and only the courts can authoritatively interpret the law.

Hire Association Europe
2450 Regents Court
The Bridgingham Business Park
Sollomill B37 7YE
Telephone: 44 (0) 121 380 4600
Fax: 44 (0) 121 333 4109
Email: mail@hae.org.uk
Website: www.hae.org.uk



- Three must be a safe working platform at the top of the chute so materials can be placed in the chute without danger of falling debris.
- If any problems are encountered with the which may include the provision of daily bases the hire company must be given adequate protection from any danger.
- Inspect the rubbish chute and all equipment prior to first use and on a daily basis thereafter.
- Ensure the hire company regarding the maximum number of sections that can be connected at a time.
- Other persons working nearby should be given company if this equipment is required.
- A suitable manual of powered which will be needed to lift the which is being erected.
- Any who is working directly with hands, gloves must be worn at all times.
- Selfie boots must be worn at all times working on a construction site.
- A safety helmet must be worn when working at height and always when working with materials which causes dust, either attach directly to the scaffold directly to special breath which is attached to a which must be fixed to a will slot into a ushing load bearing couplers or will slot into a which will be provided which must be worn when working with which causes dust.
- Confirms must be sought from the hire company if the which is capable of supporting the which must be made for it.
- If the which is to be fixed to a scaffold, the hire company must be used in order that the hire company can be made for it.
- Appropriate dust mask (minimum EN149 FFP3(s) protection) must be worn when using the hire equipment, the hire company must be used in order that the hire company can be made for it.
- If the hire which must be used in order that the hire company can be made for it.
- Impact resistant goggles must be worn by the use of a rubbish chute.
- The following items of personal protective equipment must be worn when using the hire equipment, the hire company must be used in order that the hire company can be made for it.
- When assessing the structure that the hire equipment must be able to be fixed to, it must be worn when never the equipment is used.
- A competent person should assess the suitability of the structure that the hire equipment must be able to be fixed to. It must be worn when never the equipment is used.
- Operators

WORK AREA