

Before Starting Work.

## **SITITAMA3** CEMENT MIXES AND CONTACT

- cause contact dermatitis. Wet cement mix is a substance that can
- occur when the skin reacts to certain Contact dermatitis is a rash that may .S
- Was in contact with the skin. rash occurs only where the substance usually itchy and causes flaky skin. The substances. The rash can vary but it is
- eyes and seek medical advice it you get immediately. Thoroughly rinse out your 3. Wash cement mixes off your skin
- Mild dermatitis will heal providing there is any type of cement mix in them.
- no further contact. It the rash persists, .4

## **VIBRATION - REDUCING THE** ICSI SOVICE лаці ма

- RISK
- supervisor or the hire company it you Wearing gloves can help. Ask your to think about keeping your hands warm. through the day. It is especially important you will be able to keep warm and dry are warm before you start work, and that 1. In cold conditions, make sure that you
- it, and suffer more vibration. Talk to the you may have to grip it tighter to control to work taster may cause more vibration: tor the Job. Forcing the vibrating screed Check that you have the best equipment .s залою раац
- condition: for example that the beams Make sure that the equipment is in good 3. equipment for the job. то до, то спеск ії уоц паче тпе пулі hire company about the job that you plan
- are free of hardened concrete, and that

**FHH**IRE GROUP

v:112016

- the engine runs properly.
- vesociation ⊨urope
- **3YT TEB Iludilos** The Crescent Birmingham Business Park มกอา ราบอุธุอห บอะ

- :lism3 :euoudeie

.s

11

'6

.8

.,

**'**9

**'**C

10

chinders.

**MORK AREA** 



0118 Safety Guidance

It is important to read this entire leaflet

BEFORE using the Vibrating Beam Screed

Petrol is highly flammable. Take care not to cause a fire or

Cement mixes can be harmful to eyes, lungs, and skin. Follow

any instructions given by the manufacturers of the cement

A vibrating beam screed produces high levels of vibration while

works, and how to set it up before you start on the main task.

dB(A); Safety waterproof boots to EN345 or BS1870/4972; gloves; overalls.

temporary or permanent disability must seek expert advice before using it.

in operation - see vibration - reducing the risk.

handled in a careful and controlled way.

Vibrating Beam Screed

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

Vibrating screed machines are designed to produce a flat smooth surface on large areas of

freshly laid concrete. The vibrating action reduces the amount of air trapped in the wet

The weight and vibratory action of this machine can cause injury or damage if it is not

If you have not used a vibrating screed before, familiarise yourself with how the machine

Plan how to do the job and try to foresee any problems that may occur so that you can safely

You must have at least the following items of personal protective equipment: impact resistant goggles: EN166 - B or BS2092 grade 1; ear muffs or plugs giving protection for levels up to 96

This machine must not be used by minors, or by anyone under the influence of drugs or alcohol.

This screed machine is designed for operation by able-bodied adults. Anyone with either

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting materia

from the use of any such document/material. Only Acts of Parliament and Statu have the force of law and only the courts can authoritatively interpret the law.

is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perc nave arisen from the use of any such document/material. Only Acts of Parliament and Statutory Ins









Vindenue su n'explore substances a substances of the substances of

it in domestic premises and only use it in

carbon monoxide poisoning. Never use

confined spaces could cause fatal

Using this equipment indoors or in

ignite tumes from petrol. or gas

there is a danger of explosion. It will

Do not use the vibrating screed where

locked away to keep it safe from thett.

Hired equipment should always be

that it will not get too cold overnight.

It you can, store the vibrating screed so

now so that you have suitable equipment

or your supervisor to have this put right

suitable, arrange with the hire company

If the equipment is faulty or is not

you are self employed, you should

your supervisor. Show them this leaflet. If

numbness in your fingers or hands - tell

It you have any persistent tingling or

warm and flexible. At the end of the day.

your hands and fingers to keep them

Take short breaks regularly. Exercise

nored to the beams, transienting the full

Check that the engine remains firmly

Keep warm, especially your hands.

ready for the next morning.

consider seeing a doctor.

vibration efficiently.

Μμίθ γου're working



to have arisen t

e.org.uk ©Copyright Hire Association Europe April 2011

the mixes coming into contact with your

You should wear gloves, overalls with long sleeves and full trousers to prevent

that you may have to stand and work in

(EN345 or BS1870/4972). Remember

You must wear safety waterproof boots

ear mutts or plugs giving hearing protection for this level as a minimum.

levels up to 96 dB(A)wear appropriate

This equipment is likely to cause noise

BS2092) when you are working with this

ops or environments may require a

vou use the vibrating screed. Particular

protective equipment (ppe) are the minimum that should be worn whenever

wet cement. Warn others to keep away,

Protect other people from the noise and

and that no-one is near to you or could

Make sure that the area is clear and safe

fully assessed. Mechanical extraction

and the ventilation required has been

ventilation will almost always

put barriers around your work area.

righer level of protection.

The tollowing items

must wear goggles (EN166 or

Dare skin.

wer concrete.

.inemqiue

protective e

alstract you.

required.

SHO IAHAYO

**'**G

ť

3

44 (0) 121 380 4600 44 (0) 121 333 4109 nail·

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

...C

`t

31

.s

'6

.8

-2

-9

bersonal

to

1. No smoking.

BEFUELLING

Please keep this leaflet safely as it may be required for future reference

oham Business Park

Hire Association Europe 2450 Regents Court The Crescent olibull B37 7YE



As the





move your fuel can to a safe, cool place.

Put all fuel caps back on properly, and

7. If you spill any fuel on your clothes,

e. If you spill any fuel on the ground, wipe it

Wipe any fuel off the machine. Dispose

refuelling. Do not spill any fuel on

Use a funnel and clean petrol when

Clean the filler cap and the area around it to prevent dirt falling into the fuel tank.

petore you start the machine you must

permeen pesms to ensure they produce struts, which strengthen the rigidity

machines are fitted with pretensioning

towards the top, helping to produce a

aggregate towards the bottom and brings more of the 'sand and cement'

near the surface. It vibrates the large

and reduces the amount of air trapped

machine compacts the wet concrete,

The vibrating action of the screed

move. Get neip to move it and set it up.

This machine is heavy and awkward to

do not use it - contact the hire company.

other equipment supplied with your machine. If anything is found damaged,

Check the engine, the twin beams, and

Anybody who is working near to you will also need to wear appropriate personal

10. The twin beams on some screed

11. Find out how all the controls work:

Stop the engine and let it cool down.

change them straight away.

of tuel soaked cloth carefully.

up or cover it with soil.

yourseit or the machine.

RIOW TOW TO STOP IL.

a pertectly level surface.

smooth fiat level surace.

protective equipment.

## To stop the engine, close the throttle lever, turn the fuel tap off, and turn the ON/OFF switch to OFF.

**STARTING AND STOPPING THE** 

follow the instructions below.

Check the oil and fuel levels

Open the throttle control a little.

the fuel tap on

the starter.

correctly.

Turn the ON/OFF switch to ON and turn

Make sure that you hold the drive unit

firmly so it will not move when you pull

Pull the starter cord slowly until you can

feel that the starter has engaged with the engine, then pull it quickly and strongly.

Guide the cord back so that it recoils

If the engine has started adjust the

throttle so the engine is idling. As the engine warms up open the choke lever.

Don't pull it too far, or it may break.

ENGINE

2.

3.

4.

5.

6.

8.

9.

## 1. If the hire company have given you special instructions, follow them. If not, including ear defenders, goggles and safety waterproof boots. Ensure that all the guards and safety 2. devices are correctly fitted and working properly.

For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

1. Wear

3. Stop the engine before making any adjustments.

**USING THE VIBRATING SCREED** 

your protective equipment

1.

2

3.

5.

6.

7

8

Q

10

explosion.

products.

concrete

deal with them.

- Stop work if someone approaches you. 4. 5.
- Stop the engine if leaving the machine unattended
- You must clean the vibrating screed as soon as you have finished work before
- the concrete mix goes hard.
- If your equipment does not work
- 7. properly, do not attempt to repair it.
- You may want to read this leaflet again. 8
- Please keep it until you finish work.
- 6.
- Contact the hire company.